



MOVING YOU FURTHER

25-30

33L-9A

35LN-9A



Some of the photos may include optional equipment.

 **HYUNDAI**
MATERIAL HANDLING

Your satisfaction is our priority!

New LPG Forklift with Proven Quality and Advanced Technology

Hyundai introduces a new line of 9-series LPG forklift trucks.

The newly designed 4 wheel counterbalance trucks provide every operator comfortable driving, increased productivity and easy maintenance.

High Efficiency

- Tier 4, High power engine : HMC L4KB (60PS/44.1kW)
- Reduce inching impact : Clutch protection system
- Wet disc brake

Advanced Safety

- Auto parking brake system
- Hill Start Assist Control
- Operator Presence Sensing System
- Machine inclination indication

Best Convenience

- 5.6 inch LCD color monitor
- Auto fork leveling system (OPT)
- Load weight indicator (OPT)
- 4 pieces bolt on cabin (OPT)

Easy Maintenance

- Password starting system
- Consumable item replacement cycle warning
- Rear tire cover & under cover (OPT)





Power & Performance

High Efficiency & Optimal Performance

Powerful engine and high technology systems provide you with enhanced performance and highest productivity.



Some of the photos may include optional equipment.



Powerful Engine HMC L4KB(2.4L) Engine

Market approved quality of HMC L4KB engine ensures incomparable performance, durability and additional value to the machine. Powerful and efficient engine provides excellent fuel consumption and excellent torque. (EPA/CARB Tier-IV Certified)

**HMC L4KB(2.4L) Engine
60PS/2,300rpm**



Oil cooled disc brake

The wet brakes with excellent braking power and durability offer a stable and reliable braking power. Also, an oil cooler has been added to improve durability in working environments where the frequency of brake operation is high.



Highly durable drive axle

The strengthened drive axle separable from transmission ensures low vibration and easy maintenance. The wet disc type brake is applied for easy operation, smooth response and maintenance free.



Clutch protection system

The warning lamp comes up when the operator uses half clutch and accelerator at the same time.



Fully hydrostatic power steering

The hydraulic steering system always guarantees smooth and flexible steering, preventing over-run and kick-back.




Boosting type brake valve (OPT)

The boosting type brake valve is applied for strong braking performance.

Faster Travel Speed & Gradeability

The powerful high-output engine provides greater acceleration, better gradeability and faster travel speed on any tough terrain or slope.






Easy & Comfort

Best Convenience & Optimized Ergonomics

An efficient, comfortable workspace and compact design provides enhanced performance and outstanding productivity.



Some of the photos may include optional equipment



Spacious Operator Cabin

The newly designed cabin provides wide visibility and spacious environment, ensuring all day comfort for the operator.



Some of the photos may include optional equipment



Grammer Seat (STD)

Easily adjustable suspension seat, based on a human engineering design, reduces operator fatigue and provides greater comfort.

- ELR(Emergency Locking Retractor) type seat belt as a standard
- Heating(STD) and head rest(OPT)



Optimized pedal position

On the 9-series the pedals are mounted to the console to reduce operator fatigue, and noise and dust from the engine compartment.



Adjustable steering Wheel

To achieve a comfortable drive position, the angle of the steering column can easily be adjusted by a lever on the right-hand side of the steering column.



fingertip

Ergonomically designed fingertip control levers eliminates reaches and awkward shoulder. It gives operators comfortability and efficiency.

Advanced LCD Monitor

The 5.6 inch wide screen LCD color monitor allows the operator to control the machine with ease. The monitor features speed, travel direction, battery discharge indicator and hour meter.



Main monitoring features

- Hour-meter
- Fuel level gauge (Warning-Red)
- Load weight indicator (OPT)
- Machine inclination (Warning-Red)
- Signal / Warning light
- Gear (F / N / R)
- Speedometer
- Mast tilting degree (Alarm-Red)
- Clock
- Engine temperature gauge (Warning-Red)
- Machine inclination (Warning-Red)
- Odometer

① Load Indicator (OPT)

The optional load indicator displays the load weight on the monitor. The load sensor reduces the time to check loaded weight and the alarm alerts the driver when overloaded.

② Auto Fork Leveling System (OPT)

To improve the productivity the auto fork leveling system will automatically stop the tilt movement when the mast is in a straight position.

③ Machine inclination indication


The grade (left) and slope (right) sensors are built into the MCU and provide the grade and slope status information of the vehicle connected with the road surface condition in real time.



Secure & Safety

Excellent visibility Advanced Safety

The safely designed driver's space makes your operating more comfortable.



Some of the photos may include optional equipment.

Excellent Visibility for Safe Operation

Optimized lift cylinder arrangement provides operator with wider visibility. The panoramic mirror expands the driver's view when backing up.



Safety lamps & rear reflectors

Halogen headlights and rear LED combination lights offer the driver visibility in all circumstances. Rear reflectors mounted on the counterweight enhance safety for the driver and the application.

*Full LED lamp are available. (OPT)




Low entrance height

The low entrance height ensures easy and safe access for the operator.

Various Safety System

The adoption of a high-sensitivity sensor and advanced safety system eliminates the risk of accidents.




Fork Safety Features

As the forks are being lowered, a down-control valve maintains a controlled descent speed. The down-safety valve prevents forks from dropping down in case of sudden damage of hydraulic line.



Strong overhead guard

Exceeding CEE and ANSI regulations, the overhead guard offers optimal protection combined with excellent all round visibility.



Hill Start Assist Control (HAC)

Anti Roll-back system offers protection against the machine rolling back on a ramp in combination with exceptional ramp start capabilities.



Operator Presence Sensing System

All mast and drive movements stop functioning when the operator is not in the seat.



Auto parking brake


If the operator leaves the seat while the gear lever is in neutral, the parking brake is automatically engaged to secure safety, and released upon the operator's return to the seat.



Maintenance & Convenience

Easy maintenance Various convenience devices

Ideal design for daily inspection and maintenance.
High-quality convenience devices for operator
Operator can work in the best conditions
in any environment.



Some of the photos may include optional equipment.

Large Engine Hood

Highly accessible engine compartment assures fast and efficient maintenance. The enlarged air cleaner(7") has extended service time of engine.



*Some of the photos may include optional equipment.



Waterproof & Dustproof cover

Newly developed Waterproof and Dustproof fuse box and relay box for ease of maintenance.



Rear tire & Under cover (OPT)

The rear tire cover and under cover with PE material protect the engine, radiator, and components from dusts caused by ground. Also, these options can be selected separately.



Password starting system

By granting the operation authority only to the designated driver, it is possible to manage the vehicle and prevent theft.



Rear view camera (OPT)

The rear view camera and monitor connected with the reverse switch guarantee a safe working environment.



Parking brake switch (STD) & Emergency switch (OPT)

A button-type switches enables to notify of emergency situations quickly and operate easily.



Bolt on type cabin

The bolt on type cabin consists of front side, door front, door rear, and rear side. It is easy to assemble by bolt and mount parts. Also, cabin can be selected by module or parts and air conditioner and heater are separately available for driver's convenience.

Maintenance Management				
Item	Interval	Elapse Count	Alarm	
Axle Planetary Ge...	100	2	0	✓
Transmission Oil	100	2	0	✓
Transmission Oil F...	100	2	0	✓
Hydraulic Tank Al...	250	2	0	✓
Air Cleaner Comp...	450	2	0	✓
Engine Oil Filter	500	2	0	✓

Consumable item replacement cycle warning


This indicator automatically alerts the operator of the replacement cycle of key consumable items before a failure occurs; making managing maintenance easy, and to help extend the life of the machine.

Fleet Management System(Hi FLEET)(OPT)

Hi FLEET, Hyundai material handling’s fleet management system, is the optimal operation solution for a fleet of forklifts. It connects driver and vehicle in real time.



You can see the video by scanning the QR code.



DRIVER MANAGEMENT

It is possible to certify drivers and manage their work through RFID, PIN password.

VEHICLE MANAGEMENT

You can check the operating time, battery status, and location information in real time.




SAFETY MANAGEMENT

You can check the driver's conditions and vehicle status before starting work and manage the speed and collision.

MAINTENANCE

You can keep your vehicles in optimal condition by notifying the vehicle's maintenance interval and fault codes.



New 9 Series Mast Specification

25/30/33L-9A
35LN-9A

25L-9A																							
Mast Type		Maximum Fork Height		Overall Height (Lowered)		Free Lift Height				Tilt Angle		Load Capacity without side shift				Load Capacity with side shift				TRUCK WEIGHT (UNLOADED)			
						With Load Backrest		Without Load Backrest				Single Tire		Double Tire		Single Tire		Double Tire					
		in	mm	in	mm	in	mm	in	mm	deg	deg	24 in LC	500mm LC	24 in LC	500mm LC	24 in LC	500mm LC	24 in LC	500mm LC	lb	kg	lb	kg
2-STAGE LIMITED FREE LIFT	V300	118.3	3005	79.7	2025	4.5	155	4.5	155	6	10	5000	2500	5000	2500	5000	2500	5000	2500	8161	3702	8488	3850
	*V330	130.1	3305	85.6	2175	4.5	155	4.5	155	6	10	5000	2500	5000	2500	5000	2500	5000	2500	8203	3721	8532	3870
	V350	138.0	3505	89.6	2275	4.5	155	4.5	155	6	10	5000	2500	5000	2500	5000	2500	5000	2500	8241	3738	8569	3887
	V370	145.9	3705	95.5	2425	4.5	155	4.5	155	6	10	5000	2500	5000	2500	5000	2460	5000	2500	8267	3750	8598	3900
	V400	157.7	4005	101.4	2575	4.5	155	4.5	155	6	10	5000	2500	5000	2500	5000	2380	5000	2500	8355	3790	8684	3939
	V430	169.5	4305	107.3	2725	4.5	155	4.5	155	6	6	5000	2480	5000	2500	5000	2360	5000	2500	8470	3842	8799	3991
	V450	177.4	4505	113.2	2875	4.5	155	4.5	155	6	6	5000	2430	5000	2500	4870	2310	5000	2460	8519	3864	8847	4013
	V470	185.2	4705	117.1	2975	4.5	155	4.5	155	6	6	4960	2390	5000	2500	4740	2270	5000	2380	8552	3879	8878	4027
2-STAGE FULL FREE LIFT	V500	197.0	5005	123.0	3125	4.5	155	4.5	155	6	6	4850	2330	5000	2430	4630	2210	5000	2310	8600	3901	8926	4049
	VF295 / VS295	117.2	2976	79.7	2025	33.3	845	54.2	1377	6	6	5000	2500	5000	2500	5000	2500	5000	2500	8205	3722	8543	3875
	VF325 / VS325	129.0	3276	85.1	2175	38.7	995	60.2	1527	6	6	5000	2500	5000	2500	5000	2460	5000	2500	8278	3755	8618	3909
	VF345 / VS345	136.9	3476	89.6	2275	43.1	1095	64.1	1627	6	6	5000	2500	5000	2500	5000	2380	5000	2460	8331	3779	8688	3941
3-STAGE FULL FREE LIFT	TF370/TS370	145.9	3705	71.9	1825	25.4	645	46.3	1177	6	6	5000	2500	5000	2500	5000	2460	5000	2500	8404	3812	8743	3966
	TF400/TS400	157.7	4005	75.8	1925	29.3	745	50.3	1277	6	6	5000	2500	5000	2500	5000	2380	5000	2500	8457	3836	8796	3990
	TF430/TS430	169.5	4305	79.7	2025	33.3	845	54.2	1377	6	6	5000	2440	5000	2500	5000	2320	5000	2460	8496	3854	8836	4008
	TF450/TS450	177.4	4505	83.7	2125	37.2	945	58.1	1477	6	6	5000	2410	5000	2500	4850	2290	5000	2380	8545	3876	8884	4030
	TF470/TS470	185.2	4705	85.6	2175	39.2	995	60.1	1527	6	6	4920	2360	5000	2450	4700	2240	4860	2330	8576	3890	8913	4043
	TF500/TS500	197.0	5005	89.6	2275	43.1	1095	64.1	1627	6	6	3836	1880	4940	2400	3810	1850	4720	2280	8624	3912	8962	4065
	TF550/TS550	216.7	5505	97.4	2475	51.0	1295	71.9	1827	6	6	3240	1550	4780	2310	3020	1430	4560	2190	8710	3951	9048	4104
	TF600/TS600	236.4	6005	105.3	2675	58.9	1495	79.8	2027	6	6	2930	1400	4590	2210	2710	1280	4370	2090	8854	4016	9191	4169
	TF650/TS650	256.1	6505	113.2	2875	66.7	1695	87.7	2227	3	3	2840	1350	4540	2180	2620	1230	4320	2060	8955	4062	9295	4216
	TF700/TS700	275.8	7005	121.1	3075	74.6	1895	95.6	2427	3	3	2430	1150	4370	2100	2210	930	4150	1980	9039	4100	9378	4254
4-STAGE FULL FREE LIFT	QF610	240.7	6115	85.0	2160	38.6	980	59.5	1512	3	3	3200	1600	4410	2120	2960	1480	4190	2000	9387	4258	9771	4432
	QF660	260.4	6615	92.9	2360	46.5	1180	67.4	1712	3	3	2800	1400	4230	2040	2560	1280	4010	1920	9519	4318	9901	4491
	QF700	276.2	7015	96.9	2460	50.4	1280	71.3	1812	3	3	2200	1100	1420	1980	1960	980	3900	1860	9586	4348	9969	4522
	QF745	293.9	7465	102.8	2610	56.3	1430	77.2	1962	3	3	1600	800	3420	1650	1360	680	3200	1530	9687	4394	10071	4568
	QF790	311.6	7915	108.7	2760	62.2	1580	83.1	2112	3	3	1200	600	2600	1250	960	480	2380	1130	9907	4494	10291	4668

※ : Standard

New 9 Series Mast Specification

25/30/33L-9A

35Ln-9A

30L-9A

Mast Type		Maximum Fork Height		Overall Height (Lowered)		Free Lift Height				Tilt Angle		Load Capacity without side shift				Load Capacity with side shift				TRUCK WEIGHT (UNLOADED)			
												Single Tire		Double Tire		Single Tire		Double Tire					
		With Load Backrest	Without Load Backrest	Fwd	Bwd	24 in LC	500mm LC	24 in LC	500mm LC	24 in LC	500mm LC	24 in LC	500mm LC	Single Tire	Double Tire	lb	kg	lb	kg				
		in	mm	in	mm	in	mm	in	mm	deg	deg	lb	kg	lb	kg	lb	kg	lb	kg	lb	kg	lb	kg
2-STAGE LIMITED FREE LIFT	V300	118.3	3005	80.3	2040	4.5	155	4.5	155	6	10	6000	3000	6000	3000	6000	3000	6000	3000	9030	4096	9303	4220
	*V330	130.1	3305	86.2	2190	4.5	155	4.5	155	6	10	6000	3000	6000	3000	6000	3000	6000	3000	9074	4116	9347	4240
	V350	138.0	3505	90.2	2290	4.5	155	4.5	155	6	10	6000	3000	6000	3000	6000	3000	6000	3000	9114	4134	9387	4258
	V370	145.9	3705	96.1	2440	4.5	155	4.5	155	6	10	6000	3000	6000	3000	6000	2930	6000	3000	9142	4147	9416	4271
	V400	157.7	4005	102.0	2590	4.5	155	4.5	155	6	6	6000	3000	6000	3000	6000	2820	6000	3000	9231	4187	9506	4312
	V430	169.5	4305	107.9	2740	4.5	155	4.5	155	6	6	6000	2960	6000	3000	6000	2780	6000	2950	9347	4240	9621	4364
	V450	177.4	4505	113.8	2890	4.5	155	4.5	155	6	6	6000	2920	6000	3000	5800	2740	6000	2825	9398	4263	9672	4387
	V470	185.2	4705	117.7	2990	4.5	155	4.5	155	6	6	5910	2850	6000	2930	5610	2670	5830	2755	9431	4278	9705	4402
V500	197.0	5005	123.6	3140	4.5	155	4.5	155	6	6	5820	2650	5970	2890	5520	2470	5670	2715	9482	4301	9755	4425	
2-STAGE FULL FREE LIFT	VF295 / VS295	117.2	2976	80.3	2040	33.9	860	51.7	1314	6	6	6000	3000	6000	3000	6000	3000	6000	3000	9173	4161	9444	4284
	VF325 / VS325	129.0	3276	85.1	2190	38.7	1010	60.2	1464	6	6	6000	3000	6000	3000	6000	2950	6000	3000	9250	4196	9522	4319
	VF345 / VS345	136.9	3476	90.2	2290	43.7	1110	61.6	1564	6	6	6000	3000	6000	3000	6000	2820	6000	2950	9328	4231	9599	4354
3-STAGE FULL FREE LIFT	TF370/TS370	145.9	3705	72.4	1840	26.0	660	43.9	1114	6	6	6000	3000	6000	3000	6000	2820	6000	3000	9414	4270	9685	4393
	TF400/TS400	157.7	4005	76.4	1940	29.9	760	47.8	1214	6	6	6000	3000	6000	3000	6000	2800	6000	2950	9469	4295	9738	4417
	TF430/TS430	169.5	4305	80.3	2040	33.9	860	51.7	1314	6	6	6000	2930	6000	3000	5810	2750	6000	2825	9517	4317	9786	4439
	TF450/TS450	177.4	4505	84.3	2140	37.8	960	55.7	1414	6	6	5930	2880	6000	2940	5630	2700	5830	2765	9572	4342	9843	4465
	TF470/TS470	185.2	4705	86.2	2190	39.8	1010	57.6	1464	6	6	5890	2850	5970	2900	5590	2670	5670	2725	9603	4356	9874	4479
	TF500/TS500	197.0	5005	90.2	2290	43.7	1110	61.6	1564	6	6	4630	2250	5840	2840	4495	2180	5540	2665	9654	4379	9923	4501
	TF550/TS550	216.7	5505	98.0	2490	51.6	1310	69.4	1764	6	6	3660	1750	5640	2720	3360	1570	5340	2545	9751	4423	10020	4545
	TF600/TS600	236.4	6005	105.9	2690	59.4	1510	77.3	1964	6	3	3020	1450	5450	2630	2720	1270	5150	2455	9905	4493	10174	4615
	TF650/TS650	256.1	6505	113.8	2890	67.3	1710	85.2	2164	3	3	2930	1400	5380	2590	2630	1220	5080	2415	10018	4544	10287	4666
	TF700/TS700	275.8	7005	121.7	3090	75.2	1910	93.1	2364	3	3	2540	1200	5200	2500	2240	1020	4900	2325	10112	4587	10384	4710
4-STAGE FULL FREE LIFT	QF610	240.7	6115	85.6	2175	39.2	995	57.0	1449	3	3	3400	1700	5290	2560	3040	1520	4990	2385	10317	4680	10628	4821
	QF660	260.4	6615	93.5	2375	47.0	1195	64.9	1649	3	3	3000	1500	5090	1460	2640	1320	4790	2285	10450	4740	10761	4881
	QF700	276.2	7015	97.4	2475	51.0	1295	68.9	1749	3	3	2400	1200	4960	2400	2040	1020	4660	2225	10516	4770	10827	4911
	QF745	293.9	7465	103.3	2625	56.9	1445	74.8	1899	3	3	1800	900	4830	2320	1440	720	4530	2145	10617	4816	10928	4957
	QF790	311.6	7915	109.3	2775	62.8	1595	80.7	2049	3	3	1400	700	4650	2230	1040	520	4350	2055	10838	4916	11151	5058

※ : Standard

New 9 Series

33L-9A

Mast Type		Maximum Fork Height		Overall Height (Lowered)		Free Lift Height				Tilt Angle		Load Capacity without side shift				Load Capacity with side shift				TRUCK WEIGHT (UNLOADED)			
												Single Tire		Double Tire		Single Tire		Double Tire					
		in	mm	in	mm	in	mm	in	mm	Fwd	Bwd	24 in LC	500mm LC	24 in LC	500mm LC	24 in LC	500mm LC	24 in LC	500mm LC	lb	kg	lb	kg
2-STAGE LIMITED FREE LIFT	V300	118.3	3005	83.1	2110	4.5	155	4.5	155	6	10	6500	3300	6500	3300	6500	3300	6500	3300	9636	4371	9923	4501
	*V330	130.1	3305	89.0	2260	4.5	155	4.5	155	6	10	6500	3300	6500	3300	6500	3300	6500	3300	9689	4395	9976	4525
	V350	138.0	3505	92.9	2360	4.5	155	4.5	155	6	10	6500	3300	6500	3300	6500	3300	6500	3300	9722	4410	10011	4541
	V370	145.9	3705	98.8	2510	4.5	155	4.5	155	6	10	6500	3300	6500	3300	6500	3210	6500	3300	9755	4425	10040	4554
	V400	157.7	4005	104.7	2660	4.5	155	4.5	155	6	10	6500	3300	6500	3300	6500	3120	6500	3300	9846	4466	10132	4596
	V430	169.5	4305	110.6	2810	4.5	155	4.5	155	6	6	6500	3250	6500	3300	6500	3070	6500	3250	9965	4520	10251	4650
	V450	177.4	4505	116.5	2960	4.5	155	4.5	155	6	6	6500	3190	6500	3300	6500	3010	6500	3125	10015	4543	10304	4674
	V470	185.2	4705	120.5	3060	4.5	155	4.5	155	6	6	6500	3140	6500	3240	6300	2960	6500	3065	10051	4559	10337	4689
	V500	197.0	5005	126.4	3210	4.5	155	4.5	155	6	6	6420	3100	6500	3170	6120	2920	6500	2995	10104	4583	10390	4713
2-STAGE FULL FREE LIFT	VF295 / VS295	117.2	2976	83.1	2110	36.6	930	54.5	1384	6	6	6500	3300	6500	3300	6500	3300	6500	3300	9819	4454	10099	4581
	VF325 / VS325	129.0	3276	88.3	2260	41.9	1080	60.1	1534	6	6	6500	3300	6500	3300	6500	3210	6500	3300	9899	4490	10179	4617
	VF345 / VS345	136.9	3476	89.0	2260	46.5	1180	64.3	1634	6	6	6500	3300	6500	3300	6500	3120	6500	3250	9976	4525	10254	4651
3-STAGE FULL FREE LIFT	TF370/TS370	145.9	3705	75.2	1910	28.7	730	43.9	1114	6	6	6500	3300	6500	3300	6500	3120	6500	3250	10135	4597	10414	4724
	TF400/TS400	157.7	4005	79.1	2010	32.7	830	47.8	1214	6	6	6500	3250	6500	3300	6500	3070	6500	3125	10183	4619	10463	4746
	TF430/TS430	169.5	4305	83.1	2110	36.6	930	51.7	1314	6	6	6500	3180	6500	3280	6500	3000	6500	3105	10229	4640	10509	4767
	TF450/TS450	177.4	4505	87.0	2210	40.6	1030	55.7	1414	6	6	6500	3120	6500	3220	6270	2940	6500	3045	10276	4661	10558	4789
	TF470/TS470	185.2	4705	89.0	2260	42.5	1080	57.6	1464	6	6	6350	3080	6500	3170	6050	2900	6290	2995	10306	4675	10586	4802
	TF500/TS500	197.0	5005	92.9	2360	46.5	1180	61.6	1564	6	6	5130	2500	6390	3110	4930	2390	6090	2935	10355	4697	10635	4824
	TF550/TS550	216.7	5505	100.8	2560	54.3	1380	69.4	1764	6	6	4560	2200	6170	2990	4260	2020	5870	2815	10452	4741	10732	4868
	TF600/TS600	236.4	6005	108.7	2760	62.2	1580	77.3	1964	6	6	3130	1500	5950	2870	2830	1320	5650	2695	10613	4814	10893	4941
	TF650/TS650	256.1	6505	116.5	2960	70.1	1780	85.2	2164	3	3	3060	1450	5910	2830	2760	1280	5610	2655	10719	4862	10999	4989
	TF700/TS700	275.8	7005	124.4	3160	78.0	1980	93.1	2364	3	3	2650	1250	5710	2730	2350	1080	5410	2555	10809	4903	11089	5030
4-STAGE FULL FREE LIFT	QF610	240.7	6115	87.6	2225	41.1	1045	57.0	1449	3	3	3600	1800	5930	2870	3240	1620	5630	2695	10891	4940	11182	5072
	QF660	260.4	6615	95.5	2425	49.0	1245	64.9	1649	3	3	3200	1600	5730	2770	2840	1420	5430	2595	11023	5000	11314	5132
	QF700	276.2	7015	99.4	2525	53.0	1345	68.9	1749	3	3	2600	1300	5600	2700	2240	1120	5300	2525	11089	5030	11380	5162
	QF745	293.9	7465	105.3	2675	58.9	1495	74.8	1899	3	3	2000	1000	5420	2620	1640	820	5120	2445	11184	5073	11475	5205
	QF790	311.6	7915	111.2	2825	64.8	1645	80.7	2049	3	3	1600	800	5250	2530	1240	620	4950	2355	11411	5176	11704	5309


New 9 Series Mast Specification

25/30/33L-9A
35LN-9A

35LN-9A																							
Mast Type		Maximum Fork Height		Overall Height (Lowered)		Free Lift Height				Tilt Angle		Load Capacity without side shift				Load Capacity with side shift				TRUCK WEIGHT (UNLOADED)			
						With Load Backrest		Without Load Backrest				Single Tire		Double Tire		Single Tire		Double Tire					
		in	mm	in	mm	in	mm	in	mm	Fwd	Bwd	24 in LC	500mm LC	24 in LC	500mm LC	24 in LC	500mm LC	24 in LC	500mm LC	lb	kg	lb	kg
2-STAGE LIMITED FREE LIFT	V300	118.3	3005	83.1	2110	4.5	155	4.5	155	6	10	7000	3500	7000	3500	7000	3500	7000	3500	9946	4511	10129	4594
	*V330	130.1	3305	89.0	2260	4.5	155	4.5	155	6	10	7000	3500	7000	3500	7000	3500	7000	3500	9998	4535	10181	4618
	V350	138.0	3505	92.9	2360	4.5	155	4.5	155	6	10	7000	3500	7000	3500	7000	3440	7000	3500	10033	4551	10216	4634
	V370	145.9	3705	98.8	2510	4.5	155	4.5	155	6	10	7000	3500	7000	3500	6890	3390	7000	3460	10085	4575	10268	4658
	V400	157.7	4005	104.7	2660	4.5	155	4.5	155	6	10	7000	3500	7000	3500	6730	3310	6860	3380	10156	4607	10339	4690
	V430	169.5	4305	110.6	2810	4.5	155	4.5	155	6	6	6950	3420	7000	3500	6580	3230	6710	3300	10274	4660	10457	4743
	V450	177.4	4505	116.5	2960	4.5	155	4.5	155	6	6	6850	3370	7000	3470	6470	3180	6620	3250	10326	4684	10509	4767
	V470	185.2	4705	120.5	3060	4.5	155	4.5	155	6	6	6750	3310	6930	3420	6380	3130	6530	3200	10361	4700	10544	4783
2-STAGE FULL FREE LIFT	V500	197.0	5005	126.4	3210	4.5	155	4.5	155	6	6	6600	3240	6800	3350	6250	3060	6380	3140	10413	4723	10596	4806
	VF295 / VS295	117.2	2976	83.1	2110	36.6	930	54.5	1384	6	6	7000	3500	7000	3500	7000	3500	7000	3500	10129	4595	10306	4675
	VF325 / VS325	129.0	3276	89.0	2260	41.9	1080	60.1	1534	6	6	7000	3500	7000	3500	7000	3460	7000	3500	10207	4630	10383	4710
	VF345 / VS345	136.9	3476	92.9	2360	46.5	1180	64.3	1634	6	6	7000	3500	7000	3500	6900	3400	7000	3460	10284	4665	10459	4744
3-STAGE FULL FREE LIFT	TF370/TS370	145.9	3705	75.2	1910	28.7	730	43.9	1114	6	6	7000	3500	7000	3500	6750	3320	6860	3390	10443	4737	10620	4817
	TF400/TS400	157.7	4005	79.1	2010	32.7	830	47.8	1214	6	6	6950	3440	7000	3500	6600	3240	6730	3320	10492	4759	10668	4839
	TF430/TS430	169.5	4305	83.1	2110	36.6	930	51.7	1314	6	6	6820	3360	7000	3460	6460	3170	6600	3250	10538	4780	10714	4860
	TF450/TS450	177.4	4505	87.0	2210	40.6	1030	55.7	1414	6	6	6710	3310	6890	3410	6380	3120	6510	3200	10586	4802	10762	4882
	TF470/TS470	185.2	4705	89.0	2260	42.5	1080	57.6	1464	6	6	6620	3260	6800	3360	6290	3080	6420	3160	10615	4815	10792	4895
	TF500/TS500	197.0	5005	92.9	2360	46.5	1180	61.6	1564	6	6	6490	3190	6670	3290	6160	3010	6290	3090	10665	4838	10842	4918
	TF550/TS550	216.7	5505	100.8	2560	54.3	1380	69.4	1764	6	6	4820	2340	6450	3170	4490	2190	6070	2980	10762	4882	10938	4962
	TF600/TS600	236.4	6005	108.7	2760	62.2	1580	77.3	1964	6	6	3100	1500	6230	3060	2810	1360	5870	2870	10921	4954	11098	5034
	TF650/TS650	256.1	6505	116.5	2960	70.1	1780	85.2	2164	3	3	2860	1380	6000	2950	2570	1240	5670	2770	11029	5003	11205	5083
	TF700/TS700	275.8	7005	124.4	3160	78.0	1980	93.1	2364	3	3	2570	1240	5800	2850	2280	1090	5500	2680	11118	5043	11294	5123
4-STAGE FULL FREE LIFT	QF610	240.7	6115	87.6	2225	41.1	1045	57.0	1449	3	3	3800	1900	6080	2950	3440	1720	5730	2770	11200	5080	11388	5165
	QF660	260.4	6615	95.5	2425	49.0	1245	64.9	1649	3	3	3400	1700	5880	2850	3040	1520	5530	2670	11333	5141	11521	5226
	QF700	276.2	7015	99.4	2525	53.0	1345	68.9	1749	3	3	2800	1400	5730	2780	2440	1220	5400	2600	11398	5170	11586	5256
	QF745	293.9	7465	105.3	2675	58.9	1495	74.8	1899	3	3	2200	1100	5580	2690	1840	920	5220	2520	11492	5213	11680	5298
	QF790	311.6	7915	111.2	2825	64.8	1645	80.7	2049	3	3	1800	900	5400	2600	1440	720	5070	2440	11721	5317	11909	5402


※ : Standard

New 9 Series



- Optional Items
- Fork(mm)
25L-9A : 900, 1000, 1050(STD), 1200, 1350, 1500, 1650, 1800, 2100
30/33L-9A, 35LN-9A : 900, 1050(STD), 1150, 1200, 1650, 1800, 1970, 2120, 2300, 2400
 - Integral Sideshift, Fork Positioner, Sideshift, Integral Fork Positioner with Sideshift
 - Tire : Solid(superelastic) / Non-marking / Front double tire
 - M.C.V : 4-Spool
 - Seat : Armrest, Heat, Backrest Ext, Buckle SW
 - Load Weight Indicator
 - Auto Fork Leveling System

- Rear View Camera
 - Cabin(Heater, A/C)
 - Hydraulic Pump Temperature / Pressure Indication
 - Battery Disconnect Switch(Master Switch)
 - Beacon Lamp(LED) (Amber, Red, Blue)
 - Rear work Lamp(Bulb or LED)
 - F-N-R & Horn Knob switch
 - Rear Horn with Handle
 - Finger Tip Control Lever
 - Full LED Lamp



* All specifications and photos in this catalog are subject to change for quality improvement.

New 9 Series

25/30/33L-9A
35LN-9A

Specification



Identification						
1.1	Manufacturer		Hyundai			
1.2	Manufacturer's model designation		25L-9A	30L-9A	33L-9A	35LN-9A
1.3	Drive: electric (battery or mains),diesel,petrol,fuel gas>manual		LPG	LPG	LPG	LPG
1.4	Type of operation:hand,pedestrian,standing,seated,order-picker		seated	seated	seated	seated
1.5	Load capacity / Rated load	kg	2500	3000	3300	3500
1.6	Load center distance	c mm	500	500	500	500
1.8	Load distance, center of drive axle to fork	x mm	468	468	468	468
1.9	Wheelbase	y mm	1650	1700	1700	1700
Weights						
2.1	Service weight	kg	3721	4116	4395	4535
2.2	Axle loading, loaded front / rear	kg	5491 / 731	6298 / 818	6727 / 968	6942 / 1092
2.3	Axle loading, unloaded front / rear	kg	1524 / 2197	1590 / 2526	1548 / 2847	1449 / 3085
Wheels, Chassis						
3.1	Tires : Pneumatic(P), Solid(S), Non-marking(N)		P	P	P	P
3.2	Tires size, front	Single	7.00-12-12PR	8.15-15-14PR	8.15-15-14PR	8.15-15-14PR
		Double	6.00-15-10PR	6.00-15-10PR	6.00-15-10PR	6.00-15-10PR
3.3	Tires size, rear	Single	6.50-10-12PR	6.50-10-12PR	6.50-10-12PR	6.50-10-12PR
		Double	6.50-10-12PR	6.50-10-12PR	6.50-10-12PR	6.50-10-12PR
3.4	Number of wheels front / rear (x=driven wheels)		2x / 2	2x / 2	2x / 2	2x / 2
3.5	Tires width, front	Single mm	999	1005	1005	1005
		Double mm	1153	1153	1153	1153
	Tires width, rear	mm	980	980	980	980
Basic Dimensions						
4.1	Mast / fork carriage tilt forward / backward (/)		degrees	6 / 10	6 / 10	6 / 10
4.2	Lowered mast height		h1 (mm)	2175	2190	2260
4.3	Free lift		h2 (mm)	155	155	155
4.4	Lift height		h3 (mm)	3305	3305	3305
4.5	Extended mast height		h4 (mm)	4485	4485	4485
4.7	Overhead guard height (cabin)		h5 (mm)	2160 (2170)	2180 (2190)	2180 (2190)
4.8	Seat height / standing height rel. to SIP		h7 (mm)	1187	1212	1212
4.12	Coupling height		h10 (mm)	295	320	320
4.19	Overall length		l1 (mm)	3657	3726	3782
4.20	Length to face of forks		l2 (mm)	2607	2676	2732
4.21	Overall width	Single b1 (mm)	1200	1228	1228	1228
		Double b1 (mm)	1517	1517	1517	1517
4.22	Fork dimensions(hook type)		l / e / s (mm)	1050 x 100 x 45	1050 x 122 x 45	1050 x 122 x 45
4.23	Fork carriage ISO 2328, class / type A,B		b3 (mm)	2A	3A	3A
4.24	Fork-carriage width		m1(mm)	1102	1102	1102
4.31	Ground clearance, loaded, under mast		m2(mm)	130	145	145
4.32	Ground clearance, centre of wheelbase		Ast(mm)	157	181	171
4.33	Aisle width for pallets 1,000x1,200 crossways (LxW)		Ast(mm)	4010	4081	4131
4.34	Aisle width for pallets 800x1,200 lengthways (WxL)		Wa(mm)	4210	4281	4331
4.35	Turning radius		b13 (mm)	2342	2413	2463
4.36	Smallest pivot point distance		b13 (mm)	714	731	731

Performance Data						
5.1	Travel speed, unloaded	km/h	18.0	18.9	18.9	18.9
5.2	Lift speed, loaded/ unloaded	mm/s	580 / 590	570 / 590	460 / 480	450 / 480
5.3	Lowering speed, loaded/unloaded	mm/s	500 / 450	500 / 450	500 / 450	500 / 450
5.5	Drawbar pull, loaded	kg	2686	2437	2443	2169
5.7	Gradient performance, loaded	%	35.2	28.3	26.0	24.9
5.9	Acceleration time, loaded/ unloaded(10m)	sec	-	-	-	-
5.10	Service brake		FOOT	FOOT	FOOT	FOOT
Engine						
6.1	Engine manufacturer / type		HMC/L4KB	HMC/L4KB	HMC/L4KB	HMC/L4KB
6.2	Engine power acc. to ISO 1585	kW/rpm	44.1 / 2300	44.1 / 2300	44.1 / 2300	44.1 / 2300
6.3	Maximum Torque	kgf.m/rpm	19 / 1800	19 / 1800	19 / 1800	19 / 1800
6.4	No. of cylinder / cubic capacity	EA/cc	4 / 2359	4 / 2359	4 / 2359	4 / 2359
6.5	Fuel consumption acc. To VDI cycle	ℓ /h	-	-	-	-
Other Details						
8.1	Type of drive control		PowerShift	PowerShift	PowerShift	PowerShift
8.2	Operating pressure, system / attach	bar	196 / 162	206 / 162	206 / 162	216 / 162
8.3	Oil volume (hydraulic)	l	30(60 Max.)	30(60 Max.)	30(60 Max.)	30(60 Max.)
8.4	Sound pressure level (at driver's ear according to DIN 12053)	dB(A)	80	80	80	80
8.5	Trailer coupling, type DIN		PIN	PIN	PIN	PIN

Dimension

